

Blades			Upper torque limit for adjusting an assembly with handles in Nm			
			HSA 4 0.8-2NM	HSA 4 1-5NM	TSA 6 5-14NM	
Designation	Tip <sup>(1)</sup>	Hex size, mm	(Port size 4 mm)		(Port size 6 mm)	
BLD 4 T07-0.9NM	T07	4	0.9	–	–	
BLD 4 IP07-0.9NM	7IP		1.3			
BLD 4 IP07-1.2NM	7IP					
BLD 4 T08-1.2NM	T08					
BLD 4 IP08-1.2NM	8IP		2			2.5
BLD 4 T09-2.0NM	T09					3
BLD 4 IP09-2.0NM	9IP					3.8
BLD 4 T10-3.2NM	T10					4.5
BLD 4 IP10-3.2NM	10IP					
BLD 4 T15-4.8NM	T15		2			5
BLD 4 IP15-4.8NM	IP15					
BLD 4 HEX4	SW4					
BLD 6 T20	T20	6			8	
BLD 6 T20IP	20IP				10	
BLD 6 T25	T25				13	
BLD 6 T25IP	25IP				14	
BLD 6 HEX4	SW4					
BLD 6 HEX5	SW5					
BLD 6 HEX6	SW6					

**(1) Tip designation:**

T... - Torx (hexalobular internal)

...IP - Torx Plus (Internal Plus)

SW... - Hex (Allen)

For handles with an inserted blade, the torque should not exceed the maximum value shown in the table.