

What's in the box

- BS Induction Unit
- Clamping ring
- 4 stop discs for SRKIN shrinkable holders.
- Protective gloves
- Barcode scanner
- 12 blank magnets
- Page with SRKIN parameter stickers

Not included – suitable holder adaptor – to be ordered separately

3449603	INDN BS AD HSK 32	HSK 32
3449604	INDN BS AD HSK 40	HSK 40 /HSK 50 F.B.D
3449605	INDN BS AD HSK 50	HSK 50 /HSK 63 F.B.D
3449606	INDN BS AD HSK 63	HSK 63 /HSK 80 F.B.D
3449607	INDN BS AD HSK 80	HSK 80 /HSK 100 F.B.D
3449608	INDN BS AD HSK 100	HSK 100
3449609	INDN BS AD TAPER #30	SK/BT/CAT #30
3449611	INDN BS AD TAPER #40	SK/BT/CAT #40
3449613	INDN BS AD TAPER #50	SK/BT/CAT #50
3449614	INDN BS AD C3	C3
3449615	INDN BS AD C4	C4
3449616	INDN BS AD C5	C5
3449617	INDN BS AD C6	C6
3449618	INDN BS AD C8	C8

Not included – suitable stop disc – to be ordered separately

3449266	INDN BS DISC SRK3 #6	SRK Ø 3
3449267	INDN BS DISC SRK4 #7	SRK Ø 4
3449268	INDN BS DISC SRK5 #8	SRK Ø 5
3449270	INDN BS DISC SRK6 #9	SRK Ø 6
3449271	INDN BS DISC SRK8 #10	SRK Ø 8
3449272	INDN BS DISC SRK10 #11	SRK Ø 10
3449273	INDN BS DISC SRK12 #12	SRK Ø 12

Technical data

Machine type	INDN BS INDUCTION UNIT
Clamping range	Ø3-32mm (1/8" - 1 1/4") (Carbide)
Coil	Fixed
Max. tool length	400mm (15.748")
Max. machine interface	HSK A100 / #50 taper cone
Power	8kW
Electric current supply	400V / 16A / 50 Hz - EU (480V / 15A / 60Hz – US)
Dimensions (W x D x H)	320 x 400 x 840 mm (12.599" x 15.748" x 33.071")
Weight	20 Kg (44 lb)

Needed infrastructures for INDN BS unit:

16A 5pin industrial socket

